

PRO-9500

Welltech Provision Server

Welltech PRO-9500 Server provides excellent auto-provision solution for all administrators of Welltech VoIP system. With friendly configuration interface, customers can manage VoIP CPE clients in a simple way. Configuration and software upgrade are no longertime-wasting and tiresome work. Administrator can set general update file for all CPEs for same module, or set only for some specific clients by specify their MAC address. PRO-9500 server is no doubt your best solution for client management. With this state-of-the-art tool, construction of VoIP environment is much more convenient and easy to go.

Specification

Suit For

- VoIP ISP or ISR
- MIS of Enterprise implemented VoIP system
- Any Administrator of Welltech VoIP System

Architecture

- Provision Server
- Provision Client: Configuration interface for Provision server
- VoIP CPE products

Provision Server Main Features

- Negotiate with Provision Client for uploading CPE's firmware and configuration file
- Accept request from CPE, and allow CPE to download firmware or configuration
- Support login authentication from CPE
- Support Administrator authentication from Provision Client
- Support daily log:
 - CPE Login name, IP, Port, Login Time, Logout Time, Downloaded file, Download Status, MAC
- Support Statistics:
 - Total connections
 - Current connections
 - Total files downloaded
 - Total files uploaded
- Support dual network interface for public and private network
- Support max connections limitation

Provision Client Main Features

- Set central configuration file

- Upload firmware to Provision Server
 - Bulk update
 - Individual update by specifying MAC address
- Interface to check log on Provision Server
- Check firmware and configuration file status on Provision Server
- Check CPE Status:
 - Connection log of all visited CPEs
 - CPE update log
- Support reset & restart Provision Server
- Synchronize history log for different PC that run EMS Client

Management

- Support remote upgrade Provision Server program

Physical Dimensions

- 483mm(W) x 450mm (D) x 44mm (H)
- Industrial rack mounted
- Weight: 6.92Kg

Processor & Storage

- Intel Pentium 4
- Windows XP Embedded
- 1024MB RAM
- 512 MB DOM
- Upgradable OS
- Upgradable Program

Environmental

- Operating temperature: 0~60°C
- Storage temperature: 0-60°C
- Operating humidity: 5%~95%

Certification

- CE, FCC