

IP Phone LP-305/305A

Key Features

- Multi-server registration: Can register up to 5 different servers
- 3-way Conference Bridge built-in
- Headset Jack support
- Full Duplex Speaker Phone

Application

- ISP/ITSP (Internet Telephony Service Provider)
- IP-PBX with office telephony services
- Multi-nation enterprise communication
- SOHO Telephony

Calling Features

- Call Hold
- Call Transfer
- Call Forward
- Call Waiting
- Call Conference
- DND (Do Not Disturb)
- Call List (Missed, Received, Dialed)
- 5 configurable speed dials
- Support up to 5 multi-lines

Network Support

- Fixed IP
- Dynamic Host Configuration Protocol (DHCP)
- PPPoE connection (When PPPoE disconnect, SIP-Phone can automatically re-connect)
- Behind NAT IP Sharing Device
- Support QOS by setting DSCP (Differentiated Service Code Point) parameters of VoIP packet
- Support STUN

Technical Specification

- Two 10/100 Base-T Ethernet ports with Switch inside
- LCD Configuration Password Protection
- 2*24 dot matrix LCD display
- LCD Display Time, Date, Caller ID, Call Duration
- 9 one-touch function keys: Speaker, Redial, Mute, Hold, Transfer, Message, SPEED, Conference, Headset.
- 5 LED Display: Headset, Message, Hold, Mute, Speaker
- Support Power over Ethernet (IEEE 802.3af)
- Support RFC 3261 SIP Protocol

Audio Features

- G.711 A/μ-Law, G.729, G.723
- Dynamic Jitter Buffer

Management Features

- Software Upgrade: TFTP/FTP download
- Easy ways for system configuration
 - A. LCD Front Panel
 - B. Web Browser
 - C. TELNET
 - D. Provision Server



Dimension: 215mm(W) x 71mm(H) x 198mm(D)
Weight(unit):834 grams

Certification

- CE, FCC

Power Supply

- DC 9V with Adaption 110V/230V AC Input

Operation Environment

- Humidity: 10 to 90 % (Non-condensing)
- Operational Temperature: 0 to +40°C

Storage Environment

- Humidity: 10 to 90 % (Non-condensing)
- Storage Temperature: -10 to +50°C

Order Information	
IP Phone LP-305	Standard Version
IP Phone LP-305A	Support PoE

