



Features:

- WinXP Embedded Operation System
- Support All Analogues Camera with Welltech Video Server
- Dual-type Codec (H.264 + M-JPEG)
- Dual-Monitor Display Design (Video + E-Map)
- Multiplex Design (Live, Playback, Backup, Remote Viewing)
- Hot-standby REC (Always Recording *1)
- Video Analytics Software built-in
- E-mail Alarm (inc Hard Drive Failure) Notification
- DVD Writer Backup (optional)
- Dynamic & Static IP supported
- Remote Viewing via 3G handset *2
- Up to 2,048-camera Management Capability

Notes: 1. Deduct the dead possibility caused by hard disk failure
 2. Support "Windows Mobile OS" 3G Handset ONLY

Other Components of Welltech IP System:

- Network Video Server
- Network Day&Night PoE Camera
- Network Video Recorder
- Network Matrix Decoder
- Network Alarm GPIO expansion module
- Gigabits PoE Hub



Specification

Model no.:

- WVP-165-64** : 64ch Commander Station Ultimate
- WVP-165-128** : 128ch Commander Station Ultimate
- WVP-165-2048** : 2,048ch Commander Station Ultimate

Electrical:

- Operating System : WinXP Embedded OS (DOM)
- TCP/IP : Gigabit Port (RJ-45)
- Live Display : 480pps @D1 resolution (16ch per screen)
- Playback : 480pps @D1 resolution (16ch per screen)
- Recording Resolution : CIF, VGA, D1, SXVGA)
- Built-in CD/DVD Writer : Optional
- Video Backup : USB2.0, DVD Writer
- Video Analytics : Video Loss, Motion, Smart Search & etc..
- PTZ Control : Pelco, Panasonic, Kalatel, Bosch & etc

Power Requirement:

- Power Input : 90-240 Vac, 50/ 60 Hz
- Power Consumption : 180 W (exclude hard disk's)

Mechanical:

- Housing : Metal material
- Installation : desktop
- Dimension : 16ch, 32ch & 48ch : 430 x 390 x 155 mm
- Weight : 16ch, 32ch & 48ch : 9 Kgs

Environment:


- Operating : 0 to 50 °C, 10% to 80% R.H. (non-condensing)
- Storage : (-)10 to (+) 70 °C, 5% to 95% (non-condensing)

- Approvals** : CE, FCC, RoHS

Technology



File Size



Video Quality

