

## Welltech Product Release Note

Date:2010/03/15

<b>Division:</b>	SDD1	<b>Releaser:</b>	Songyo
<b>Model Name:</b>	WellGate2608, 2680 and 2644	<b>Object:</b>	<input type="checkbox"/> H.W. <input checked="" type="checkbox"/> S.W.
<b>Subject:</b>	release firmware : wg26xx_ap_107		
<b>Release contents</b>			
<b>Bug Fixed</b>			
<ol style="list-style-type: none"><li>1. Fixed the RTCP stop sending issue after first RTCP was sent.</li><li>2. Fixed a few G.711u packets were sent to IP network during T.38 was activated.</li><li>3. Only allow 1 RTP session to be received and played when 2 concurrent RTP sessions was received.</li><li>4. When DHCP server is used on Wellgate 26xx, the DHCP offer message doesn't use the modified configuration on Wellgate 26xx. It was fixed.</li><li>5. When FXO port is connected, a short sharp noise might be transmitted to IP Site caller. It was fixed.</li><li>6. Network failure detecting time was improved.</li></ol>			
<b>Feature and Function Added</b>			
<ol style="list-style-type: none"><li>1. Support HTTP, FTP and WellEMS9510 auto provision feature.</li><li>2. Support media change by using UPDATE method</li><li>3. Support NAT traversal method for STUN or static IP mapping</li><li>4. Support HTTPS web server</li><li>5. FXO port will only go ON-HOOK after FXS port was ON-HOOK to avoid the incoming call cannot be passed to FXS (PABX mode at WellGate 2644 only)</li><li>6. Support fake ringing (before SIP command 180 is received)</li><li>7. Support RFC3325 P-Asserted-Identity header.</li><li>8. Support three types of register mode: 1: One Proxy, 2: Active-Active, 3:Active-Backup</li></ol>			
<b>WEB Configuration Item Changed</b>			
<b>Application Block Diagram</b>			
<b>Hyperlink</b>			
WELLTECH WEB Site: <a href="http://www.welltech.com">http://www.welltech.com</a>			
Firmware Download: <a href="http://www.welltech.com/support/26xx.htm">http://www.welltech.com/support/26xx.htm</a>			
User Manual: <a href="http://www.welltech.com/support/26xx.htm">http://www.welltech.com/support/26xx.htm</a>			
<b>Note</b>			